

SOLBERG® RE-HEALING™ 3x3 FLUORINE-FREE SP-100



FAST FACTS

- First UL-listed fluorine-free foam for both hydrocarbon and polar solvent (water miscible) fuels using standard sprinkler heads
- Biodegradable and non-persistent
- UL 162 Listed
- Fresh, salt & brackish water compatible
- Fast knockdown & extinguishing performance tested
- Great foam stability to extended water discharge
- Excellent burnback performance
- Compatible with multiple equipment systems
- Contains no siloxanes

DESCRIPTION

SOLBERG® RE-HEALING™ 3x3 FLUORINE-FREE SP-100 foam concentrate contains cutting edge technology that is not persistent, contains no silicone/siloxane chemistries, and contains no intentionally added PFAS chemicals. SOLBERG RE-HEALING 3x3 FLUORINE-FREE SP-100 is designed for extinguishing and securing both Class B (hydrocarbon fuel and polar solvent fuel) and deep-seated Class A fires. This fluorine-free foam concentrate is a combination of proprietary hydrocarbon surfactants and additives delivering excellent foaming, vapor sealing, and stability properties for attacking and securing both shallow and fuel in-depth fires.

APPLICATIONS

SOLBERG RE-HEALING 3x3 FLUORINE-FREE SP-100 is specifically designed for sprinkler applications to extinguish and secure Class B (hydrocarbon fuel and polar solvent) fuels. This technology allows it to be used successfully through both standard and air-aspirated sprinkler heads on both hydrocarbon and polar solvent fuel fires. SOLBERG RE-HEALING 3x3 FLUORINE-FREE SP-100 can also be used with low-expansion discharge devices, including a variety of nozzles and monitors. It is fully compatible and easily proportioned with standard firefighting equipment, including in-line inductors, self-inducting nozzles, fire truck pumps, bladder tanks, pump skids, balanced pressure systems, and more.



CERTIFICATIONS

SOLBERG RE-HEALING 3x3 FLUORINE-FREE SP-100 has been Underwriters Laboratories listed with the following equipment:

RATIO CONTROLLERS

FIXED ORIFICE RATIO CONTROLLERS

Size	Flow Rate (GPM)
2"	52-255
2.5"	155-470
3"	210-570
4"	430-1370
6"	877-2893
8"	2324-5001

SOLBERG® RE-HEALING™ 3X3 FLUORINE-FREE SP-100

STANDARD SPRINKLER HEADS

RELIABLE – K-FACTOR 8.0 – RA6222

Fuel Type	Style	Min. Application Rate (GPM/sqft)	Min. Inlet Pressure (PSI)
Hydrocarbon	Upright	0.22	7.0
Alcohols	Upright	0.37	18.8

RELIABLE – K-FACTOR 8.0 – R1027

Fuel Type	Style	Min. Application Rate (GPM/sqft)	Min. Inlet Pressure (PSI)
Hydrocarbon	Upright	0.22	7.0
Alcohols	Upright	0.40	22.0

RELIABLE – K-FACTOR 8.0 – RA6212

Fuel Type	Style	Min. Application Rate (GPM/sqft)	Min. Inlet Pressure (PSI)
Hydrocarbon	Pendent	0.22	7.0
Alcohols	Pendent	0.37	18.8

RELIABLE – K-FACTOR 8.0 – R1017

Fuel Type	Style	Min. Application Rate (GPM/sqft)	Min. Inlet Pressure (PSI)
Hydrocarbon	Pendent	0.22	7.0
Alcohols	Pendent	0.37	18.8

VIKING – K-FACTOR 11.2 – VK536

Fuel Type	Style	Min. Application Rate (GPM/sqft)	Min. Inlet Pressure (PSI)
Hydrocarbon	Pendent	0.32	7.0
Alcohols	Pendent	0.48	16.1

FOAM WATER SPRINKLER HEADS (ASPIRATED)

TYCO FIRE & BUILDING PRODUCTS – K-FACTOR 3.0 - MODEL B-1 AND STAR SPRINKLER INC.

Fuel Type	Style	Min. Inlet Pressure (PSI)	Min. Application Rate (GPM/sqft)
Hydrocarbon	Pendent/Upright	30.0	0.16
Alcohols	Pendent/Upright	30.0	0.16
Ketones	Pendent	30.0	0.16

SOLBERG® RE-HEALING™ 3X3 FLUORINE-FREE SP-100

USAGE RATE

The proportioning rate is 3% for both hydrocarbons and polar solvents.

TYPICAL PROPERTIES		FOAM PROPERTIES	
Specific Gravity, g/cm ³	1.000 - 1.040	Dilution Rate	3%
pH @ 68°F	6.5 - 7.5	Low Expansion Foam (UNI-86)	
Viscosity (#4 @ 30 rpm)	3000 - 5000	Foam Expansion Index	7 - 8
Freezing Point, °F	16°F	Drain Time	>30 minutes
Lowest Temperature for Use, °F	35°F		

* Brookfield DV Viscometer

INSPECTION

SOLBERG RE-HEALING 3X3 FLUORINE-FREE SP-100 or a premix solution should be tested annually per National Fire protection Association (NFPA 11) and EN-13565-2 standards. A sample of the foam concentrate should be sent to the manufacturer or qualified third-party lab to confirm physical properties and foam quality meet the specifications of the foam as originally supplied as per the requirements of NFPA 11 and EN-13565-2.

PACKAGING

The product is supplied in 5 gallon pails, 55 gallon drums, and 265 gallon totes.

PART NUMBER	DESCRIPTION
10001267	5 gallon pail
10001266	55 gallon drum
10001265	265 gallon tote
20000098	Bulk

STORAGE/MATERIAL COMPATIBILITY

SOLBERG RE-HEALING 3X3 FLUORINE-FREE SP-100 should be stored between 35°F - 120°F, preferably in the original containers. It is compatible with multiple materials of construction found in firefighting equipment. For questions about material of construction compatibility consult Perimeter Solutions technical services.

CAUTIONS

Foams should not be used in contact with electrical equipment or with chemical products that can react with water. It is recommended to avoid contact of the foam concentrate with skin. In case of eye splashes, wash with plenty of water. In case of ingestion do not induce vomiting, drink water and seek medical advice.

Contains no intentionally added PFAS.

SOLBERG® RE-HEALING™ 3X3 FLUORINE-FREE SP-100



Solutions That Save.

FOR MORE INFORMATION

Contact any of our worldwide Perimeter Solutions Fire Safety offices or visit:

www.Perimeter-Solutions.com

UNITED STATES

1520 Brookfield Avenue
Green Bay, WI 54313

Tel: +1 (920) 593-9445

salesfoamusa@perimeter-solutions.com

EMEA

Polígono Industrial de Baiña, Parcela 23
33682 Baiña-Mieres (Asturias) – Spain

Tel: +34 985 24 29 45

salesfoameea@perimeter-solutions.com

ASIA PACIFIC

3 Charles Street
St Marys NSW 2760 – Australia

Tel: +61 2 9673 5300

salesfoamapac@perimeter-solutions.com

perimeter-solutions.com

NOTICE PERIMETER SOLUTIONS MAKES NO REPRESENTATIONS OR WARRANTIES AS TO THE COMPLETENESS OR ACCURACY OF THE INFORMATION INCLUDED HEREIN. THE INFORMATION CONTAINED HEREIN IS NOT INTENDED TO PROVIDE REGULATORY, LEGAL OR EXPERT ADVICE RELATING TO THE PRODUCTS, ITS APPLICATION OR USES. NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A RECOMMENDATION TO USE ANY PRODUCT, PROCESS, EQUIPMENT OR FORMULATION IN CONFLICT WITH ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS, AND PERIMETER SOLUTIONS MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, THAT THE USE THEREOF WILL NOT INFRINGE ON ANY INDUSTRIAL PROPERTY OR INTELLECTUAL PROPERTY RIGHTS. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.